

# Window Patch Antennas

#### <u>Part#</u>

# Frequency Band

02518B	VHF 140-155 MHz
02518D	VHF 155-180 MHz
02630T	UHF 405-420 MHz
02630X	UHF 435-480 MHz
02630Z	UHF 470-515 MHz

#### **Applications**

Mobile Vehicle Glass Mount Installations

## Tuning

Factory tuned or inline fine tuning pot board

#### Features

 $\checkmark$ 

- ✓ Easy Installation saves you time and money
  - Interior-mounting/no drilling, magnets, scratches, suction cups, or clips
  - No need to remove for car washing
  - Multi-polarisation reduces interference and dropped calls
    - o Reduces static and signal drop-off
    - High gain regardless of signal orientation
    - Signal clarity in rural and urban areas
- ✓ Wider bandwidth extends signal
  - Covers broader bandwidth
  - Leading-edge technology
    - Field-proven high performance products
    - o State-of-the-art products

## Mountings

Vehicle Glass Mount Installations

## **Specifications**

Gain: Power Rating:	3dB Low Power up to 35 Watts (CW Po	wer)	
Operating VSWR:	1.5:1	Weight:	0.300Kg
Colour:	Graphite	Termination:	5m RG58 cable un terminated
Size:	90 (W) x 95 (H) x 0.33 (D) mm	Case Material:	Flame retardant substrate

# Packaging

Poly Bag, one antenna per bag

# Warranty

12 month (Please refer to Benelec Standard Warranty Terms and Conditions)



BENELEC.COM.AU