

## DATASHEET

### Window Patch Antennas

**Part#**    **Frequency Band**

<b>02518B</b>	VHF 140-155 MHz
<b>02518D</b>	VHF 155-180 MHz
<b>02630T</b>	UHF 405-420 MHz
<b>02630X</b>	UHF 435-480 MHz
<b>02630Z</b>	UHF 470-515 MHz



### APPLICATIONS

Mobile Vehicle Glass Mount Installations

### TUNING

Factory tuned or inline fine tuning pot board

### FEATURES

- ✓ Easy Installation saves you time and money
  - Interior-mounting/no drilling, magnets, scratches, suction cups, or clips
  - No need to remove for car washing
- ✓ Multi-polarisation reduces interference and dropped calls
  - Reduces static and signal drop-off
  - High gain regardless of signal orientation
  - Signal clarity in rural and urban areas
- ✓ Wider bandwidth extends signal
  - Covers broader bandwidth
- ✓ Leading-edge technology
  - Field-proven high performance products
  - State-of-the-art products



### MOUNTINGS

Vehicle Glass Mount Installations

### Specifications

---

---

<b>Gain:</b>	3dB	<b>Weight:</b>	0.300Kg
<b>Power Rating:</b>	Low Power up to 35 Watts (CW Power)	<b>Termination:</b>	5m RG58 cable un terminated
<b>Operating VSWR:</b>	1.5:1	<b>Case Material:</b>	Flame retardant substrate
<b>Colour:</b>	Graphite		
<b>Size:</b>	90 (W) x 95 (H) x 0.33 (D) mm		

### Packaging

Poly Bag, one antenna per bag

### Warranty

12 month (Please refer to Benelec Standard Warranty Terms and Conditions)