

NEXEDGE®

One Radio with Multi-Protocol Support

NX-3720HG/3820HG

VHF/UHF DIGITAL TRANSCEIVER

NXDN™ **DMR**



DMR
-based
TRUNKING **T3&S**

DMR >>>>>
Auto Slot
Select >>>>>

FleetSync® **5-tone** **GPS** **Bluetooth®**

This adaptable mobile radio supports both NXDN and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise- and operation-critical applications. Designed with flexibility in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. And providing greater freedom of installation, the radio's front panel can be used as a remote control head (this requires an optional accessories). Additionally, for expansion capability a software license certification system facilitates extensive customization.

PRODUCT HIGHLIGHTS

- **Multi-protocol digital radio:** Designed to operate under an NXDN or DMR digital, and FM analog protocols
- **Mixed Digital & FM Analog Operation** allows gradual migration at your own pace
- **4-Line** Basic Frame (2 lines of icon & key guide) / 14 Characters
- **4-Line** Text Message Frame (2 Lines of Text, icon & key guide) Note: The number of lines may vary depending on the display language (character set).
- **7-Color LED** indicator
- External and Internal Speaker Switching
- **Built-in GPS** Receiver for effective fleet management
- **Built-in Bluetooth** for hands-free operation
 - Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option; availability depends on the model)
- Renowned **KENWOOD Audio Quality with Active Noise Reduction (ANR)** that utilizes built-in DSP
- Software **DES** and AES Encryptions for Digital protocols
- **MIL-STD-810 C/D/E/F/G**



- **Single Remote Head** operation (Requires optional control head interface kit)

GENERAL FEATURES

- Audio Output Power (4 Watts at 4Ω)
- Paging Call
- Emergency Call
- Status / Text Message
- Remote Stun / Kill / Check

DIGITAL - NXDN MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

DIGITAL - DMR MODE

- S-Trunking
- DMR Tier III Trunking
- DMR Tier II Conventional
- DMR Auto Slot Select
- Site Roaming
- 12.5 kHz Two-slot TDMA channels
- Call Interruption
- Dual-slot Direct Mode
- Enhanced Encryption
- Energy Efficient

ANALOG - FM MODE

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, DTMF, 5-tone
- Built-in Voice Inversion Scrambler



OPTIONAL ACCESSORIES

<ul style="list-style-type: none"> KMC-35/36 MICROPHONE [IP54/55] (without/with 12-keypad) 	<ul style="list-style-type: none"> KRK-18H CONTROL HEAD INTERFACE KIT 	<ul style="list-style-type: none"> KCT-18 IGNITION SENSE CABLE (requires KCT-60) 	<ul style="list-style-type: none"> KCT-71 REMOTE CONTROL CABLE (M2: 5.2m, M3: 7.6m) 	<ul style="list-style-type: none"> KLF-2 LINE FILTER 
<ul style="list-style-type: none"> KMC-65/66 MICROPHONE [IP54/55] (without/with 12-keypad) 	<ul style="list-style-type: none"> KRK-19B CONTROL HEAD REMOTE KIT 	<ul style="list-style-type: none"> KCT-23 DC POWER CABLE 	<ul style="list-style-type: none"> KCT-72 CONNECTION CABLE (for Remote Control Head) 	<ul style="list-style-type: none"> KMB-10 KEY LOCK ADAPTER 
<ul style="list-style-type: none"> KES-5 (A) EXTERNAL SPEAKER (40 W max input, requires KCT-60) 	<ul style="list-style-type: none"> KCT-60 CONNECTION CABLE (D-sub 15 to Molex 15 Pin Connector) 	<ul style="list-style-type: none"> KCT-73MIC EXTERNAL MIC KIT (Requires KCT-60 or KCT-72) 	<ul style="list-style-type: none"> KCT-74PTT EXTERNAL PTT KIT (Requires KCT-60 or KCT-72) 	<ul style="list-style-type: none"> KRA-40G GPS ACTIVE ANTENNA 
				<ul style="list-style-type: none"> KPG-180AP OTAP MANAGER (PC software) 

All accessories and options may not be available in all markets. Contact an authorized KENWOOD dealer for details and complete list of all accessories and options.

SPECIFICATIONS

GENERAL	NX-3720HG	NX-3820HG
Frequency Range	136-174 MHz	400-470 MHz
Max. Channels per Radio	Up to 1000 channels with option	
Number of Channels	512	
Number of Zones	128	
Channel Spacing	Analog 12.5 / 25*1 kHz Digital 6.25 / 12.5 kHz	
Operating Voltage	13.6 V DC ± 15 %	
Current Drain	Standby 0.45 A RX 2.3 A TX 9 A	
Operating Temperature	-30°C to +60°C	
Frequency Stability (-30°C to +60°C; +25°C Ref.)	± 0.5 ppm	
Antenna Impedance	50 Ohms	
Dimensions (W x H x D) *Projections not included	160 x 43 x 160 mm	
Weight (net)	1.2 kg	

*1 Over 12.5 kHz channel spacings are not included in the models sold in the USA or US territories. Specifications are measured according to applicable standards. Specifications shown are typical and subject to change without notice, due to advancements in technology.

RECEIVER	NX-3720HG	NX-3820HG
Sensitivity	NXDN 6.25 kHz Digital, 3 % BER	0.20 µV
	NXDN 12.5 kHz Digital, 3 % BER	0.25 µV
	DMR 12.5 kHz Digital, 5 % BER	0.25 µV
	DMR 12.5 kHz Digital, 1 % BER	0.45 µV
	Analog, 12 dB SINAD	0.25 µV
Selectivity	Analog @ 12.5 kHz	70 dB
	Analog @ 25 kHz	80 dB
Intermodulation	75 dB	
Spurious Rejection	80 dB	
Audio Distortion	2 %	
Audio Output	4 W	
TRANSMITTER	NX-3720HG	NX-3820HG
RF Power Output	50 W / 30 W / 5 W	45 W / 30 W / 5 W
Spurious Emission	-73 dB	-75 dB
FM Hum & Noise	Analog @ 12.5 kHz	40 dB
	Analog @ 25 kHz	45 dB
Audio Distortion	2 %	
Digital Protocol	ETSI TS 102 361-1, -2, -3, -4	
Emission Designator	16K0F3E*, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

APPLICABLE MIL-STD & IP*2

MIL Standards	Methods / Procedures					
	810C	810D	810E	810F	810G	
Low Pressure	500.1/ I	500.2/ I, II	500.3/ I, II	500.4/ I, II	500.5/ I, II	
High Temperature	501.1/ I, II	501.2/ I, II	501.3/ I, II	501.4/ I, II	501.5/ I, II	
Low Temperature	502.1/ I	502.2/ I, II	502.3/ I, II	502.4/ I, II	502.5/ I, II	
Temp. Shock	503.1/ I	503.2/ I	503.3/ I	503.4/ I, II	503.5/ I	
Solar Radiation	505.1/ I	505.2/ I	505.3/ I	505.4/ I	505.5/ I	
Rain	506.1/ I, II	506.2/ I, II	506.3/ I, II	506.4/ I, III	506.5/ I, III	
Humidity	507.1/ I, II	507.2/ II, III	507.3/ II, III	507.4	507.5/ II	
Salt Fog	509.1/ I	509.2/ I	509.3/ I	509.4	509.5	
Dust	510.1/ I	510.2/ I	510.3/ I	510.4/ I, III	510.5/ I	
Vibration	514.2/ VIII, X	514.3/ I	514.4/ I	514.5/ I	514.6/ I	
Shock	516.2/ I, II, V	516.3/ I, IV, V	516.4/ I, IV, V	516.5/ I, IV, V	516.6/ I, IV, V	
International Protection Standards						
Dust & Water	IP54: RF Deck; IP55: Remote Control Head					

*2 All interfaces must be fully sealed with appropriate covers or by designated genuine accessories.

• The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by JVCKENWOOD Corporation is under license. • NXDN™ is a trademark of JVCKENWOOD Corporation and Icom Inc. • NEXEDGE® is a registered trademark of JVCKENWOOD Corporation. • FleetSync® is a registered trademark of JVCKENWOOD Corporation. • All other trademarks are the property of their respective holders.

