DATASHEET PART NO: 02525

8 FOOT VHF MARINE ANTENNA AIS SUITABLE **

The 02525 antenna is a marine antenna for use in the VHF 156-162MHz marine band (**including AIS1 and AIS2 Channels). The antenna is housed in a white, smooth and rugged fiberglass radome, and comes complete with five metres of low loss cable. The antenna comes with a Male UHF Plug connector (04104) allowing connection to the Transceiver. The antenna can be used with a range of alternative optional mountings.

APPLICATIONS

Marine VHF

TUNING

Factory tuned – requires no further adjustment.


FEATURES

- Smooth white fibreglass radome
- 5 meters low loss cable
- **Chromed Brass fittings**
- Matched adjustable bases (bases optional extra)
- White cable


MOUNTING OPTIONS

<u>02735S</u>	Two way Knuckle Small.
02735	Two way Knuckle (Glass nylon filled)
<u>02737</u>	Two way Knuckle Stainless Steel.
<u>02738</u>	Two way Knuckle Chromed Brass.
027381	Rail mount – Stainless Steel.

VSWR



RADIATION PATTERN



SPECIFICATIONS

Freuency	156 – 162 MHz <1.6:1
Gain	Unity
Impedance	50 Ohms nominal
Polarisation	Vertical
Radiation	Omni directional
Termination	Male UHF plug – to be fitted by the customer
Base Materials	Fiberglass and Chromed Brass
Antenna Length (L)	2380 mm

PACKAGING

Cardboard Tube, one antenna per tube, 45 (OD) mm x 2430 (L) mm, Gross Weight: 1.2 Kg

WARRANTY

3 years (Please refer to Benelec Terms & Conditions)

