

Part No **02742** **Base, UHF female (SO-239) - 5/16" male**

The **02742 UHF – 5/16 base** allows a coax with PL-259 (UHF plug) to be connected to the standard Australian 5/16" female ferrule connectors typically used on ground plane whip antennas. It is a quality Nickel plated product on the UHF side & brass on the 5/16 side. Unlike silver plated connectors it has high resistance to tarnishing. It can be mounted to a bulkhead, a bracket, a box etc.

The UHF shield screw thread connection conforms to the proper UHF PL-259 standard imperial thread (unlike some competitor 'metricized' parts).

Applications

An example of applicable antenna styles includes:

- 02152** 27MHz CB Epoxy 3' Whip, Redback
- 02153** 27MHz CB Epoxy 4' Whip, MiniStick
- 02613 UHF CB 477MHz Mini-flex whip

Base, UHF female - 5/16" male



Features

- ✓ Brass metal parts
- ✓ Gold Plated centre pin UHF connector
- ✓ Nickel plated (all else)
- ✓ Teflon Dielectric, Delrin outer
- ✓ Reliable, Robust, Durable
- ✓ Suitable up to 520MHz
- ✓ Threads conform to proper imperial standards for PL-259

Packaging

Each: N.W. 64g; PolyBag 10x: G.W. 650g;
Box 100x: G.W. 7kg;

Warranty

12 months (Please refer to [Benelec Terms & Conditions](#))