

Part № 04114 UHF Jack, flanged, Panel mount, with nut

The 04114 mount is essentially a flanged SO-239 (UHF female) connector designed to mount on many mobile radios and mate externally with antenna coax that have PL-259 UHF male plugs; and internally via a soldered centre and solder tab shield. The construction features Brass metal parts with Nickel or Gold plated surfaces as appropriate. It utilizes a bakelite dielectric. The shield screw thread connection conforms to the proper UHF PL-259 standard imperial thread (unlike some competitor 'metricized' parts).

Applications

Terminating Coaxial cable with radio equipment

04114 side



- ✓ Nickel Plated brass.
- ✓ Gold plated centre-pin
- ✓ Bakelite dielectric
- ✓ Reliable, Robust, Durable
- ✓ Solder tab centre connection
- ✓ Solder Tab shield connection (1.7mm hole)
- ✓ 18mm AF nut
- ✓ Useable up to 520MHz
- ✓ Flange 20mm across
- ✓ Requires 15.9mm panel hole





Similar products

- 04112 <u>4 hole</u> flange mount SO-239 (UHF female)
- 04113 <u>2 hole</u> flange mount SO-239 (UHF female)

Packaging

Individual, N.W. 16g

Warranty

12 months (Please refer to **Benelec Terms & Conditions**)

BENELEC.COM.AU

04114 rear