

DATASHEET SKU: 048309L

4.3-10 DIN Plug Right Angled for LL400



Braid Jacket

Cable Stripping Dimensions (mm)

The 048309L QMA plug is a 4.3-10 DIN Plug. This connector has SUCO plated body and silver-plated centre pin. PTEF insulator and silicon rubber O-ring are both provided for protection. It also has a nickel-plated ferrule and coupling cap.

FEATURES

- SUCO Plated Body
- Silver Plated Centre Pin
- PTEF Insulator
- Silicon Rubber O-Ring
- Nickel Plated Ferrule and Coupling Cap
- 50 Ohm
- Reliable, Robust & Durable
- **RoHS Complaint**

APPLICABLE CABLES

This 048309L is applicable for LMR400 Coaxial Cable.

MATERIALS & PLATING

	Description	Material	Surface Plating
1	Body	Brass	SUCO
2	Coupling Cap	Brass	Nickel
3	Insulator	PTFE	N/A
4	Centre Contact	Brass	Silver Plated
5	O-Ring	Silicone Rubber	N/A
6	Ferrule	Brass	Nickel

PACKAGING

Each: Net Weight - 85g Poly Bag: 50 pcs - G.W. 4.25kg Box: 500 Pcs - G.W. 42.5kg

WARRANTY

12 months (Please refer to Benelec Terms & Conditions)

Website: benelec.au