

DATASHEET

Replacement Battery for Motorola XTS 2500 2500 mAh Lithium-ion



SPECIFICATIONS

Chemistry	Capacity	V	Cell Origin	CHG. Temp.	DHG. Temp.
Li-ion	2500 mAh	7.5	Panasonic	0°C to 40°C	-20°C to 60°C

For Use with Two Way Radio Models:	XTS2500/XTS1500/MT1500/PR1500
Replacement for OEM Battery No.:	NNTN7335/NNTN9857/NNTN9858/ NNTN9815/ NNTN9816

Housing Material	Polycarbonate
Sealing Method	Ultrasonic Welding
External Contacts Material	Gold Plated Nickel
Internal Cell Pack Welding	Pure Nickel Tabs, Spot Welded
LWH dimension (mm)	126.50×58×35
With Belt Clip	Yes
IMPRES compatible	Yes

SAFETY FEATURES

The battery pack incorporates safety devices designed to prevent damage, overheating, fire or explosion in case of non-typical events such as accidental short-circuit or use of a wrong or faulty charger. Individual electrical cells comprise a resealable safety vent to prevent the buildup of internal pressure.

(Li-ion(7335) battery packs contain circuitry designed to prevent overcharging and over-discharging, which can harm the internal cells and lead to premature battery end-of-life, and swelling in extreme cases.)

**This product was developed and is continually tested in conjunction with original device and charging equipment.
It is guaranteed for complete compatibility with these.
Specifications of all components used meet or exceed that of equipment.**