

DATASHEET

SKU: 101208

Benelec 2m LL195 SMA Plug to N Plug Lead



The 101208 is a prepared Coaxial Lead of 2m in length. It uses Benelec **056031** LL195 low loss coaxial cable with 04206 N-types male crimp plug at one end and a **040013** SMA male plug at the other. Both connectors have Heatshrink protecting cable entry.

FEATURES

- Characteristic Impedance 50 Ohm
- VSWR: ≤ 1.2 (0 – 3 GHz)

PACKAGING

Sealed Poly Bag: 1 per bag

NW 0.3 kg (0.7 lb),

GW 0.32 kg (0.71 lb)

WARRANTY

1 Years Please refer to ([Benelec Terms & Conditions](#))

RF LOSS (APPROX)

800 MHz	2.23 dB
2000 MHz	7.74 dB

INSTALLATION

The SMA connector is not weatherproof and is not recommended for use outdoors.

The N-Type plug is weatherproof however when used outdoors it is recommended that any outdoor connections need to be sealed with Self-amalgamating tape, such as Benelec **5052219BK**, to provide long term weather seal.

Instructions for use of self-amalgamating tape:

Remove separator of tape, elongate to double the length. Wrap continuously, half overlapping each turn, the complete coaxial joint. For complete protection also apply one or two layers of PVC Electrical Tape over the self-amalgamating tape.

Website: benelec.au